



FOCUS TECH PROCESS CHEMICALS

Technical Data Sheet

Focus Tech FS-72/OL

Photoresist Stripper

Product Description

FS-72/OL is a photoresist stripper concentrate formulated specifically for use with today's multipurpose and plating photoresists. FS-72/OL is formulated to break the resist into very small piece sizes to aid in removal from fine and/or overplated features without the use of glycol ethers. FS-72/OL strips quickly at very low concentrations and leaves the copper surface clean and free of oxidation. FS-72/OL is designed to completely remove the tenacious adhesion promoters used in many of today's photoresists.

Physical Properties

Specific gravity: 1.0
pH: > 13
Appearance: clear, light amber liquid
Flash point: > 200 °F

Analytical Procedure

Materials required:

1. 250 ml Erlenmeyer flask
2. 20 ml pipette
3. 1.0N hydrochloric acid
4. bromocresol purple indicator

Procedure:

1. Pipette 20 mls of working solution into the Erlenmeyer flask and add 100 mls of DI water.
2. Add 5 drops of bromocresol purple indicator.
3. Titrate with hydrochloric acid to a lasting color change. Typical color change is purple to yellow but will be dependent on the resist dye color.

Calculation:

$$\% \text{ v/v FS-72/OL} = \text{mls 1.0N HCl used} \times 0.646$$

Operating Parameters

Concentration: 4 - 8% v/v
Temperature: 120 – 140 °F

Storage

Store in original containers above 40 °F.

Safety

CAUTION! FS-72/OL concentrates and working solutions contain strong alkaline ingredients. Avoid contact with eyes, skin and clothing. Wear chemical handler's gloves, goggles and protective clothing when handling. Read and understand Material Safety Data Sheet before using this product.

Notice

The information and recommendations, contained herein, regarding this product are, to the best of our knowledge, true and accurate. We make no guarantee of results because the conditions of actual use are beyond our control. We assume no liability for damages or penalties resulting from the use of this product or following our recommendations. Our recommendations and suggestions for use of this product are not intended to grant license to operate under or infringe any patent.