

185HR LAM

Effective Date: 10/27/2022

■ Pumafast ■ Standard

Grade	Thickness	Construction	Base/Overall	1/1	1/H	2/2	H/H
185HR	.0030	1-1080	BSE	●	●	●	●
	.0040	1-2116	BSE	●	●	●	●
		2-106	BSE	●	●		●
	.0050	1-2116	BSE	●	●	●	●
		2-1080	BSE	●	●	●	●
	.0060	1-1652	BSE	●	●	●	●
		2-1080	BSE	●			●
	.0080	1-7628	BSE	●	●	●	●
		2-2116	BSE	●	●	●	●
		2-3313	BSE	●	●		●
	.0100	2-2116	BSE	●	●	●	●
	.0120	2-1652	BSE	●	●	●	●
	.0140	2-7628	BSE	●	●	●	●
	.0180	1-2116/2-7628	BSE	●	●	●	●
	.0210	3-7628	BSE	●		●	●
	.0240	3-7628	BSE	●			●
	.0280	4-7628	BSE	●		●	●
	.0310	4-7628	BSE				●
	.0390	5-7628	BSE	●		●	●
	.0470	6-7628	BSE	●			●
	.059A	1-2116/7-7628	OVR			●	
		8-7628	OVR	●		●	●
	.093A	1-2116/12-7628	OVR			●	
13-7628		OVR	●			●	
.125A	1-2116/17-7628	OVR	●		●	●	

Standard Sheet Size: 49 x 37G

Alternate sizes stocked based on usage. Please reach out to your customer service contact for details.