

# 370HR LAM

Effective Date: 1/3/2023

■ Pumafast ■ Standard

Grade	Thickness	Construction	Base/Overall	1/1	1/H	2/2	H/H
370HR	.0020	1-106	BSE	●	●	●	●
	.0025	1-1080	BSE	●	●	●	●
	.0030	1-2113	BSE	●	●	●	●
	.0035	1-2113	BSE	●	●	●	●
		2-106	BSE	●	●		●
	.0040	1-106/1-1080	BSE	●	●	●	●
		1-2116	BSE	●	●	●	●
	.0050	1-106/1-2113	BSE	●	●	●	●
		1-1652	BSE	●	●	●	●
	.0060	1-1080/1-2113	BSE	●	●	●	●
		1-1652	BSE	●		●	●
	.0070	1-7628	BSE	●		●	●
	.0080	1-7628	BSE	●	●		●
		2-2116	BSE	●	●	●	●
	.0100	2-1652	BSE	●	●	●	●
	.0120	2-1080/1-7628	BSE	●	●	●	●
	.0140	2-7628	BSE	●	●	●	●
	.0150	2-7628	BSE	●			
	.0180	1-2116/2-7628	BSE	●	●	●	●
	.0210	3-7628	BSE	●	●	●	●
	.0240	1-1080/3-7628	BSE	●		●	●
	.0280	4-7628	BSE	●		●	●
	.0310	1-1080/4-7628	BSE	●		●	●
	.0390	1-2116/5-7628	BSE	●		●	●
	.047A	1-2116/6-7628	OVR	●			●
	.059A	8-7628	OVR	●		●	●
	.093A	13-7628	OVR	●		●	●
	.125A	18-7628	OVR	●			

**Standard Sheet Size: 49 x 37G**

Alternate sizes stocked based on usage. Please reach out to your customer service contact for details.