

# EM-370(Z) LAM

Effective Date: 9/26/2024

■ Pumafast ■ Standard

Grade	Thickness	Construction	Base/Overall	S1/S1 (RTF)	S1/SH (RTF)	S2/S1 (RTF)	S2/S2 (RTF)	SH/SH (RTF)
EM-370(Z)	.0020	1067x1	BSE	●	●		●	●
	.0025	1078x1	BSE	●	●	●	●	●
	.0030	1086x1	BSE	●	●		●	●
	.0035	1037x2	BSE	●	●	●	●	●
		3313x1	BSE	●	●		●	●
	.0040	0106x2	BSE	●	●	●	●	●
		3313x1	BSE	●	●		●	●
	.0042	2116x1	BSE	●	●	●	●	●
	.0045	1067x2	BSE	●	●		●	●
	.0050	1067x2	BSE	●	●		●	●
		1078x2	BSE	●	●		●	●
		2116x1	BSE	●	●	●	●	●
	.0060	1086x2	BSE	●	●	●	●	●
	.0080	3313x2	BSE	●	●		●	●
	.0100	2116x2	BSE	●	●		●	●
	.0140	7628x2	BSE	●	●		●	●
	.0150	7629x2	BSE	●	●	●	●	●
	.0210	7628x3	BSE	●	●		●	●
	.0280	7628x4	BSE	●	●		●	●
	.0310	7629x4	BSE					●
.0590A	7628x4 7629x4	OVR	●	●		●	●	

**Standard Sheet Size: 49.2 x 37.2G**

Alternate sizes stocked based on usage. Please reach out to your Technical Account Manager or Inside Sales Manager for details.