

AR-85HP LAM

Effective Date: 6/3/2025

Pumafast Standard

Grade	Thickness	Construction	Base/Overall	S1/S1 (RTF)	S1/SH (RTF)	S2/S1 (RTF)	S2/S2 (RTF)	S2/SH (RTF)	SH/SH (RTF)
85HP	.0025	1086x1	BSE	●	●		●		●
	.0030	1086x1	BSE	●	●		●		●
	.0033	1067x2	BSE	●	●		●		●
		1086x1	BSE	●	●		●		●
	.0035	3313x1	BSE	●	●		●		●
	.0040	1067x1 1086x1	BSE	●	●	●	●		●
		2116x1	BSE	●	●		●		●
	.0045	1067x1 1086x1	BSE	●	●		●		●
	.0050	1067x1 3313x1	BSE	●	●		●		●
		1086x2	BSE	●	●	●	●	●	●
	.0060	1067x1 2116x1	BSE	●	●	●	●	●	●
		1086x2	BSE	●	●	●	●	●	●
	.0080	3313x1 2116x1	BSE	●	●	●	●		●
	.0100	1086x2 2116x1	BSE	●	●	●	●		●
	.0120	2116x3	BSE	●	●		●		●
	.0140	2116x3	BSE	●	●		●		●
	.0180	1506x3	BSE	●	●	●	●		●
	.0200	1086x1 1506x3	BSE	●	●	●	●		●
	.0390	3313x1 1506x6	BSE	●	●		●		●
	.0590	1506x10	BSE	●	●		●		●

Standard Sheet Size: 48.5 x 54.5G

Alternate sizes stocked based on usage. Please reach out to your Technical Account Manager or Inside Sales Manager for details.