

AR-85HP LAM

Effective Date: 11/26/2025

■ Pumafast ■ Standard

Grade	Thickness	Construction	S1/S1 (RTF)	S1/SH (RTF)	S2/S1 (RTF)	S2/S2 (RTF)	S2/SH (RTF)	SH/SH (RTF)
85HP	.0025 bse	1086x1	●	●		●		●
	.0030 bse	1086x1	●	●		●		●
	.0033 bse	1067x2	●	●		●		●
		1086x1	●	●		●		●
	.0035 bse	3313x1	●	●		●		●
	.0040 bse	1067x1 1086x1	●	●	●	●		●
		2116x1	●	●		●		●
	.0045 bse	1067x1 1086x1	●	●		●		●
	.0050 bse	1067x1 3313x1	●	●		●		●
		1086x2	●	●	●	●	●	●
	.0060 bse	1067x1 2116x1	●	●	●	●	●	●
		1086x2	●	●	●	●	●	●
	.0080 bse	3313x1 2116x1	●	●	●	●		●
	.0100 bse	1086x2 2116x1	●	●	●	●		●
	.0120 bse	2116x3	●	●		●		●
	.0140 bse	2116x3	●	●		●		●
	.0180 bse	1506x3	●	●	●	●		●
	.0200 bse	1086x1 1506x3	●	●	●	●		●
	.0280 bse	2116x1 1506x4	●	●		●		●
	.0390 bse	3313x1 1506x6	●	●		●		●
.0590 bse	1506x10	●	●		●		●	

Standard Sheet Size: 49.2 x 37.2G

Alternate sizes stocked based on usage. Please reach out to your Technical Account Manager or Inside Sales Manager for details.