

EM-370(Z) LAM

Effective Date: 11/26/2025

■ Pumafast ■ Standard

Grade	Thickness	Construction	S1/S1 (RTF)	S1/SH (RTF)	S2/S1 (RTF)	S2/S2 (RTF)	SH/SH (RTF)
EM-370(Z)	.0020 bse	1067x1	●	●		●	●
	.0025 bse	1078x1	●	●	●	●	●
	.0030 bse	1086x1	●	●		●	●
	.0035 bse	1037x2	●	●	●	●	●
		3313x1	●	●		●	●
	.0040 bse	0106x2	●	●	●	●	●
		3313x1	●	●		●	●
	.0042 bse	2116x1	●	●	●	●	●
	.0045 bse	1067x2	●	●		●	●
	.0050 bse	1078x2	●	●		●	●
		2116x1	●	●	●	●	●
	.0060 bse	1086x2	●	●	●	●	●
	.0080 bse	3313x2	●	●		●	●
	.0100 bse	2116x2	●	●		●	●
	.0140 bse	7628x2	●	●		●	●
	.0150 bse	7629x2	●	●	●	●	●
	.0210 bse	7628x3	●	●		●	●
	.0280 bse	7628x4	●	●		●	●
	.0310 bse (.0324ovr)	7629x4					●
	.0576 bse (.0590ovr)	7628x4 7629x4					●

Standard Sheet Size: 49.2 x 37.2G

Alternate sizes stocked based on usage. Please reach out to your Technical Account Manager or Inside Sales Manager for details.